

INSTRUCTIONS FOR USE
PRODUCT SPECIFIC INFORMATION
ONLY ON THIS PAGE

TEGERA® 517

Synthetic leather glove, winter-lined, synthetic leather, polyester, fleece, Cat. II, black, green, chrome free, waterproof, hook-and-loop, for precision work



EN 420:2003 + A1:2009
EN 388:2016 1121X
EN 511:2006 111

EN 420:2003 + A1:2009
EN 388:2016 1121X
EN 511:2006 111



OUTER MATERIAL SPECIFICATION Polyurethane, polyester, natural latex
MIDDLE MATERIAL SPECIFICATION Polyethylene
INNER MATERIAL SPECIFICATION Polyester

EU-TYPE EXAMINATION 2777 Satra Technology Europe Ltd Braconrow Business Park, Clonee, Dublin 15, Dublin, Ireland

UKCA-TYPE EXAMINATION 0321 Satra Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

UK CA

6 PAIRS

ONLY FOR EUROPEAN ECONOMIC COMMUNITY CUSTOMS UNION MEMBERS
ПРОДУКЦИЯ СООТВЕТСТВУЕТ ТРЕБОВАНИЯМ ТР 019/2011
«О БЕЗОПАСНОСТИ СРЕДСТВ ИНДИВИДУАЛЬНОЙ ЗАЩИТЫ»

EJENDALS AB
Limagenvägen 28, SE-799 32 Leksand, Sweden
Phone +46 (0)247 360 00 | Fax +46 (0)247 360 10
info@ejendals.com | order@ejendals.com | www.ejendals.com
Declaration of Conformity → www.ejendals.com/conformity

INSTRUCTIONS FOR USE - CATEGORY II
SEE FRONT PAGE FOR PRODUCT SPECIFIC INFORMATION
EN

Carefully read these instructions before using this product.

EXPLANATION OF PICTOGRAMS 0 = Below the minimum performance level for the given individual hazard 'X' = Not submitted to the test or test method not suitable for the glove design or material

EN 388:2016 A. Abrasion resistance Min. 0; Max. 4
B. Blade cut resistance Min. 0; Max. 5
C. Tear resistance Min. 0; Max. 4
D. Puncture resistance Min. 0; Max. 4
E. Cut Resistance Min. 0; Max. 4
F. Impact Protection P=Pass

EN 511:2006 A. Korroosivien kemikaalien vaikutus
B. Kontaktin aiheuttama lämpö
C. Vedenpitävyys
D. Puhdistusaineiden vaikutus
E. Puhdistusaineiden vaikutus
F. Puhdistusaineiden vaikutus

EN 420:2003 + A1:2009 FITTING AND SIZING: All sizes comply with the EN 420:2003+A1:2009 for comfort, fit and dexterity. If not explained on the front page. If the short model symbol is shown on the front page, the glove is shorter than a standard glove, in order to enhance the comfort for special purposes - for example

EN 420:2003 + A1:2009 STORAGE AND TRANSPORT: Ideally stored in dry and dark condition in the original package, between +10° - +30°C
INSPECTION BEFORE USE: Check that the glove does not present holes, cracks, tears, colour change etc. if the product becomes damaged, it should be disposed of immediately
SHELF LIFE: The nature of the materials used in this product means that the life of this product cannot be determined as it will be affected by many factors such as storage conditions, usage etc.

EN 420:2003 + A1:2009 CARE AND MAINTENANCE: The user bears sole responsibility for submitting the product to mechanical washing after use, as unknown substances can contaminate the product during use and may affect the performance levels of the product. To care for your product, we recommend that you rinse in cold water and line dry in room temperature.
DISPOSAL: According to local environmental legislation.

EN 420:2003 + A1:2009 LATEX FREE YES NO
BRUKSANVISING - KATEGORI II
SE FRAMSIDAN FÖR SPECIFIK PRODUKTINFORMATION
SV

Läs dessa instruktioner noggrant innan du använder produkten. FÖRSÄKRING OM ÖVERENSSTÄMMELSE

EN 388:2016 A. Skärningsstånd Min. 0; Max. 4
B. Nålingsstånd Min. 0; Max. 5
C. Pungteststånd Min. 0; Max. 4
D. Pungteststånd Min. 0; Max. 4
E. Pungteststånd Min. 0; Max. 4
F. Pungteststånd Min. 0; Max. 4

EN 511:2006 A. Korroosivien kemikaalien vaikutus
B. Kontaktin aiheuttama lämpö
C. Vedenpitävyys
D. Puhdistusaineiden vaikutus
E. Puhdistusaineiden vaikutus
F. Puhdistusaineiden vaikutus

EN 420:2003 + A1:2009 FITTING AND SIZING: All sizes comply with the EN 420:2003+A1:2009 for comfort, fit and dexterity. If not explained on the front page. If the short model symbol is shown on the front page, the glove is shorter than a standard glove, in order to enhance the comfort for special purposes - for example

EN 420:2003 + A1:2009 STORAGE AND TRANSPORT: Ideally stored in dry and dark condition in the original package, between +10° - +30°C
INSPECTION BEFORE USE: Check that the glove does not present holes, cracks, tears, colour change etc. if the product becomes damaged, it should be disposed of immediately
SHELF LIFE: The nature of the materials used in this product means that the life of this product cannot be determined as it will be affected by many factors such as storage conditions, usage etc.

EN 420:2003 + A1:2009 CARE AND MAINTENANCE: The user bears sole responsibility for submitting the product to mechanical washing after use, as unknown substances can contaminate the product during use and may affect the performance levels of the product. To care for your product, we recommend that you rinse in cold water and line dry in room temperature.
DISPOSAL: According to local environmental legislation.

EN 420:2003 + A1:2009 LATEX FREE JA NEI
KÄYTTÖOHJEET - KATEGORIA II
KATSO ETUSIVU TUOTEKOHTAISTEN TIETOJEN OSASTA
FI

Lue nämä ohjeet huolellisesti ennen tuotteen käyttöä. VARMISTUSTENKAIKUISUUKAUKSET

EN 388:2016 A. Hankauskästävyys Min. 0; Max. 4
B. Villin leikkauksen vastustus Min. 0; Max. 5
C. Repäisykestävyys Min. 0; Max. 4
D. Pungtestään Min. 0; Max. 4
E. Villonkestävyys TDM Min. 0; Max. 4
F. Iiskunkestävyys P=Hyväksytty

EN 511:2006 A. Korroosivien kemikaalien vaikutus
B. Kontaktin aiheuttama lämpö
C. Vedenpitävyys
D. Puhdistusaineiden vaikutus
E. Puhdistusaineiden vaikutus
F. Puhdistusaineiden vaikutus

EN 420:2003 + A1:2009 FITTING AND SIZING: All sizes comply with the EN 420:2003+A1:2009 for comfort, fit and dexterity. If not explained on the front page. If the short model symbol is shown on the front page, the glove is shorter than a standard glove, in order to enhance the comfort for special purposes - for example

EN 420:2003 + A1:2009 STORAGE AND TRANSPORT: Ideally stored in dry and dark condition in the original package, between +10° - +30°C
INSPECTION BEFORE USE: Check that the glove does not present holes, cracks, tears, colour change etc. if the product becomes damaged, it should be disposed of immediately
SHELF LIFE: The nature of the materials used in this product means that the life of this product cannot be determined as it will be affected by many factors such as storage conditions, usage etc.

EN 420:2003 + A1:2009 CARE AND MAINTENANCE: The user bears sole responsibility for submitting the product to mechanical washing after use, as unknown substances can contaminate the product during use and may affect the performance levels of the product. To care for your product, we recommend that you rinse in cold water and line dry in room temperature.
DISPOSAL: According to local environmental legislation.

EN 420:2003 + A1:2009 LATEX FREE JA NEI
KÄYTTÖOHJEET - KATEGORIA II
KATSO ETUSIVU TUOTEKOHTAISTEN TIETOJEN OSASTA
FI

INSTRUCTIONS FOR USE - CATEGORY II
SEE FRONT PAGE FOR PRODUCT SPECIFIC INFORMATION
EN

Carefully read these instructions before using this product.

EXPLANATION OF PICTOGRAMS 0 = Below the minimum performance level for the given individual hazard 'X' = Not submitted to the test or test method not suitable for the glove design or material

EN 388:2016 A. Abrasion resistance Min. 0; Max. 4
B. Blade cut resistance Min. 0; Max. 5
C. Tear resistance Min. 0; Max. 4
D. Puncture resistance Min. 0; Max. 4
E. Cut Resistance Min. 0; Max. 4
F. Impact Protection P=Pass

EN 511:2006 A. Korroosivien kemikaalien vaikutus
B. Kontaktin aiheuttama lämpö
C. Vedenpitävyys
D. Puhdistusaineiden vaikutus
E. Puhdistusaineiden vaikutus
F. Puhdistusaineiden vaikutus

EN 420:2003 + A1:2009 FITTING AND SIZING: All sizes comply with the EN 420:2003+A1:2009 for comfort, fit and dexterity. If not explained on the front page. If the short model symbol is shown on the front page, the glove is shorter than a standard glove, in order to enhance the comfort for special purposes - for example

EN 420:2003 + A1:2009 STORAGE AND TRANSPORT: Ideally stored in dry and dark condition in the original package, between +10° - +30°C
INSPECTION BEFORE USE: Check that the glove does not present holes, cracks, tears, colour change etc. if the product becomes damaged, it should be disposed of immediately
SHELF LIFE: The nature of the materials used in this product means that the life of this product cannot be determined as it will be affected by many factors such as storage conditions, usage etc.

EN 420:2003 + A1:2009 CARE AND MAINTENANCE: The user bears sole responsibility for submitting the product to mechanical washing after use, as unknown substances can contaminate the product during use and may affect the performance levels of the product. To care for your product, we recommend that you rinse in cold water and line dry in room temperature.
DISPOSAL: According to local environmental legislation.

EN 420:2003 + A1:2009 LATEX FREE YES NO
BRUKSANVISING - KATEGORI II
SE FRAMSIDAN FÖR SPECIFIK PRODUKTINFORMATION
SV

Läs dessa instruktioner noggrant innan du använder produkten. FÖRSÄKRING OM ÖVERENSSTÄMMELSE

EN 388:2016 A. Skärningsstånd Min. 0; Max. 4
B. Nålingsstånd Min. 0; Max. 5
C. Pungteststånd Min. 0; Max. 4
D. Pungteststånd Min. 0; Max. 4
E. Pungteststånd Min. 0; Max. 4
F. Pungteststånd Min. 0; Max. 4

EN 511:2006 A. Korroosivien kemikaalien vaikutus
B. Kontaktin aiheuttama lämpö
C. Vedenpitävyys
D. Puhdistusaineiden vaikutus
E. Puhdistusaineiden vaikutus
F. Puhdistusaineiden vaikutus

EN 420:2003 + A1:2009 FITTING AND SIZING: All sizes comply with the EN 420:2003+A1:2009 for comfort, fit and dexterity. If not explained on the front page. If the short model symbol is shown on the front page, the glove is shorter than a standard glove, in order to enhance the comfort for special purposes - for example

EN 420:2003 + A1:2009 STORAGE AND TRANSPORT: Ideally stored in dry and dark condition in the original package, between +10° - +30°C
INSPECTION BEFORE USE: Check that the glove does not present holes, cracks, tears, colour change etc. if the product becomes damaged, it should be disposed of immediately
SHELF LIFE: The nature of the materials used in this product means that the life of this product cannot be determined as it will be affected by many factors such as storage conditions, usage etc.

EN 420:2003 + A1:2009 CARE AND MAINTENANCE: The user bears sole responsibility for submitting the product to mechanical washing after use, as unknown substances can contaminate the product during use and may affect the performance levels of the product. To care for your product, we recommend that you rinse in cold water and line dry in room temperature.
DISPOSAL: According to local environmental legislation.

EN 420:2003 + A1:2009 LATEX FREE JA NEI
KÄYTTÖOHJEET - KATEGORIA II
KATSO ETUSIVU TUOTEKOHTAISTEN TIETOJEN OSASTA
FI

Lue nämä ohjeet huolellisesti ennen tuotteen käyttöä. VARMISTUSTENKAIKUISUUKAUKSET

EN 388:2016 A. Hankauskästävyys Min. 0; Max. 4
B. Villin leikkauksen vastustus Min. 0; Max. 5
C. Repäisykestävyys Min. 0; Max. 4
D. Pungtestään Min. 0; Max. 4
E. Villonkestävyys TDM Min. 0; Max. 4
F. Iiskunkestävyys P=Hyväksytty

EN 511:2006 A. Korroosivien kemikaalien vaikutus
B. Kontaktin aiheuttama lämpö
C. Vedenpitävyys
D. Puhdistusaineiden vaikutus
E. Puhdistusaineiden vaikutus
F. Puhdistusaineiden vaikutus

EN 420:2003 + A1:2009 FITTING AND SIZING: All sizes comply with the EN 420:2003+A1:2009 for comfort, fit and dexterity. If not explained on the front page. If the short model symbol is shown on the front page, the glove is shorter than a standard glove, in order to enhance the comfort for special purposes - for example

INSTRUCTIONS FOR USE - CATEGORY II
SEE FRONT PAGE FOR PRODUCT SPECIFIC INFORMATION
EN

Carefully read these instructions before using this product.

EXPLANATION OF PICTOGRAMS 0 = Below the minimum performance level for the given individual hazard 'X' = Not submitted to the test or test method not suitable for the glove design or material

EN 388:2016 A. Abrasion resistance Min. 0; Max. 4
B. Blade cut resistance Min. 0; Max. 5
C. Tear resistance Min. 0; Max. 4
D. Puncture resistance Min. 0; Max. 4
E. Cut Resistance Min. 0; Max. 4
F. Impact Protection P=Pass

EN 511:2006 A. Korroosivien kemikaalien vaikutus
B. Kontaktin aiheuttama lämpö
C. Vedenpitävyys
D. Puhdistusaineiden vaikutus
E. Puhdistusaineiden vaikutus
F. Puhdistusaineiden vaikutus

EN 420:2003 + A1:2009 FITTING AND SIZING: All sizes comply with the EN 420:2003+A1:2009 for comfort, fit and dexterity. If not explained on the front page. If the short model symbol is shown on the front page, the glove is shorter than a standard glove, in order to enhance the comfort for special purposes - for example

EN 420:2003 + A1:2009 STORAGE AND TRANSPORT: Ideally stored in dry and dark condition in the original package, between +10° - +30°C
INSPECTION BEFORE USE: Check that the glove does not present holes, cracks, tears, colour change etc. if the product becomes damaged, it should be disposed of immediately
SHELF LIFE: The nature of the materials used in this product means that the life of this product cannot be determined as it will be affected by many factors such as storage conditions, usage etc.

EN 420:2003 + A1:2009 CARE AND MAINTENANCE: The user bears sole responsibility for submitting the product to mechanical washing after use, as unknown substances can contaminate the product during use and may affect the performance levels of the product. To care for your product, we recommend that you rinse in cold water and line dry in room temperature.
DISPOSAL: According to local environmental legislation.

EN 420:2003 + A1:2009 LATEX FREE YES NO
BRUKSANVISING - KATEGORI II
SE FRAMSIDAN FÖR SPECIFIK PRODUKTINFORMATION
DA

Läs instruksioneerne grundigt, før ibrugtagning af dette produkt. ÖVERENSSTÄMMELSESRKLERING

EN 388:2016 A. Skärningsstånd Min. 0; Max. 4
B. Nålingsstånd Min. 0; Max. 5
C. Pungteststånd Min. 0; Max. 4
D. Pungteststånd Min. 0; Max. 4
E. Pungteststånd Min. 0; Max. 4
F. Pungteststånd Min. 0; Max. 4

EN 511:2006 A. Korroosivien kemikaalien vaikutus
B. Kontaktin aiheuttama lämpö
C. Vedenpitävyys
D. Puhdistusaineiden vaikutus
E. Puhdistusaineiden vaikutus
F. Puhdistusaineiden vaikutus

EN 420:2003 + A1:2009 FITTING AND SIZING: All sizes comply with the EN 420:2003+A1:2009 for comfort, fit and dexterity. If not explained on the front page. If the short model symbol is shown on the front page, the glove is shorter than a standard glove, in order to enhance the comfort for special purposes - for example

EN 420:2003 + A1:2009 STORAGE AND TRANSPORT: Ideally stored in dry and dark condition in the original package, between +10° - +30°C
INSPECTION BEFORE USE: Check that the glove does not present holes, cracks, tears, colour change etc. if the product becomes damaged, it should be disposed of immediately
SHELF LIFE: The nature of the materials used in this product means that the life of this product cannot be determined as it will be affected by many factors such as storage conditions, usage etc.

EN 420:2003 + A1:2009 CARE AND MAINTENANCE: The user bears sole responsibility for submitting the product to mechanical washing after use, as unknown substances can contaminate the product during use and may affect the performance levels of the product. To care for your product, we recommend that you rinse in cold water and line dry in room temperature.
DISPOSAL: According to local environmental legislation.

EN 420:2003 + A1:2009 LATEX FREE JA NEI
KÄYTTÖOHJEET - KATEGORIA II
KATSO ETUSIVU TUOTEKOHTAISTEN TIETOJEN OSASTA
FI

Lue nämä ohjeet huolellisesti ennen tuotteen käyttöä. VARMISTUSTENKAIKUISUUKAUKSET

EN 388:2016 A. Hankauskästävyys Min. 0; Max. 4
B. Villin leikkauksen vastustus Min. 0; Max. 5
C. Repäisykestävyys Min. 0; Max. 4
D. Pungtestään Min. 0; Max. 4
E. Villonkestävyys TDM Min. 0; Max. 4
F. Iiskunkestävyys P=Hyväksytty

EN 511:2006 A. Korroosivien kemikaalien vaikutus
B. Kontaktin aiheuttama lämpö
C. Vedenpitävyys
D. Puhdistusaineiden vaikutus
E. Puhdistusaineiden vaikutus
F. Puhdistusaineiden vaikutus

EN 420:2003 + A1:2009 FITTING AND SIZING: All sizes comply with the EN 420:2003+A1:2009 for comfort, fit and dexterity. If not explained on the front page. If the short model symbol is shown on the front page, the glove is shorter than a standard glove, in order to enhance the comfort for special purposes - for example

EN 420:2003 + A1:2009 LATEX FREE JA NEI
KÄYTTÖOHJEET - KATEGORIA II
KATSO ETUSIVU TUOTEKOHTAISTEN TIETOJEN OSASTA
FI